

Parameters of AquaMini

Model	SC970	SC971	SC972
PERFORMANCE CONDITION: Air 27°C/ Water 27°C/ Humid. 80%			
Heating capacity (kW)	3,5	5,6	7,2
C.O.P.	5,0	5,9	5,8
PERFORMANCE CONDITION: Air 15°C/ Water 26°C/ Humid. 70%			
Heating capacity (kW)	2,4	3,5	4,8
C.O.P.	3,8	4,1	4,3
TECHNICAL SPECIFICATIONS			
Advised pool volume(m ³)	0~12	5~20	10~35
Operating Air Temperature (°C)	10~43°C		
Power supply	230V/1Ph/50Hz		
Plug & Play	Yes		
Heat exchanger	Titanium in PVC		
Casing	Galvanized Steel Casing		
Gas	R32		
Rated input power (kW)	0,63	0,85	1,12
Rated input current (A)	2,7	3,7	4,9
Sound pressure 1m dB(A)	46,0	47,0	48,0
Sound pressure 10m dB(A)	26,0	27,0	28,0
Advised water flux (m ³ /h)	1~2	2~2.5	2.5~3.5
Water connection (mm)	32/ 38		
Net dimension LxWxH (mm)	523*330*490	703*330*490	713*330*640
Net weight(Kg)	26,0	36,0	43,5
Qty per 20'FT / 40'HQ (sets)	228/468	168/336	120/252

* : Above data is subject to modification without notice.