

Model	X26-10P	X26-12P
Advised pool volume (m3)	18~35	25~40
Operating air temperature (°C)		
Performance Condition: Air 26°C, Water 26°C, Humidity 80%		
Heating capacity (kW) in Turbo mode	10,0	12,0
Heating capacity (kW) in Smart mode	8,0	9,0
COP	21.6~7.6	23.2~7.9
COP at 50% capacity	14,4	15,0
Performance Condition: Air 15°C, Water 26°C, Humidity 70%		
Heating capacity (kW) in Turbo mode	6,6	8,5
Heating capacity (kW) in Smart mode	5,3	6,4
COP	7.9~5.4	8.8~5.6
COP at 50% capacity	7,2	7,5
Performance Condition: Air 7°C, Water 26°C, Humidity 90%		
Heating capacity (kW) in Turbo mode	5,1	6,8
COP	6.8~4.5	7.0~4.9
Sound pressure at 1m dB(A)	36.9~43.9	38.1~45.4
Sound pressure of 50% capacity at 1m dB(A)	37,9	39,1
Sound pressure at 10m dB(A)	16.9~23.9	18.1~25.4
Compressor		
Heat exchanger		
Casing		
Power supply		
Rated input power at air 15°C (kW)	0.13~1.22	0.15~1.52
Rated input current at air 15°C (A)	0.57~5.3	0.65~6.61
Advised water flux (m³/h)	2~4	2~4
Water pipe in-out size (mm)		
Net Dimension LxWxH (mm)	923×427×661	923×427×661
Net weight (kg)	67	67
Qty per 20'FT / 40'HQ (sets)	79/168	79/168
Gas (g)	750	750
GWP		
CO2 equivalent (tonnes)	0,00002	0,00002

XP26 Specification

X26-14P	X26-17P	X26-20P	X26-23P	X26-27P
30~50	35~60	40~65	45~75	55~90
-20~43				

14,2	17,0	20,0	22,5	27,0
11,7	13,9	15,5	17,6	22,5
21.9~7.6	22~7.3	23.0~7.3	26.2~7.4	21.1~7.4
15,0	14,8	14,9	15,8	15,2

9,1	11,2	13,7	15,7	18,2
7,5	9,2	10,6	12,3	15,0
8~5.2	8.8~5.2	8.4~5.1	9.2~5.3	8.1~5.5
7,3	7,5	7,3	7,8	7,3

7,4	9,5	11,5	12,5	15,6
7~4.4	7.1~4.4	7.0~4.2	7.2~4.3	6.8~4.5
38.1~46.3	41.3~47.2	41.9~47.9	42.2~49.9	41.1~50.3
40,6	43	42,8	43,6	44,4
18.1~26.3	21.3~27.2	21.9~27.9	22.2~29.9	21.1~30.3

Twin-rotary DC-inverter

Lightning heat exchanger

Aluminum-alloy Casing

230V~/1Ph/50Hz

0.19~1.75	0.21~2.16	0.25~2.68	0.27~2.96	0.37~3.31
0.83~7.61	0.91~9.39	1.09~11.65	1.17~12.87	1.61~14.39
3~4	4~6	4~6	6.5~8.5	8~10

50

1120×427×661	1112×427×760	1160×427×760	1146×536×955	1146×536×955
75	85	86	110	113
63/138	42/138	42/90	34/72	34/72

950	1000	1150	1300	1500
0,02				

0,00002	0,00002	0,00002	0,00003	0,00003
---------	---------	---------	---------	---------

X26-27PT	X26-33P	X26-33PT	X26-41PT
55~90	65~105	65~105	75~120
27,0	32,5	32,5	41,0
22,5	27,1	27,1	34,3
20.6~7.2	21.7~7.2	20.9~7.1	21.1~7.2
15,0	14,8	14,7	14,7
18,2	22,1	22,1	28,2
15,0	18,4	18,4	23,5
8.0~5.4	8.3~5.3	8~5.2	8.1~4.9
7,2	7,4	7,4	7,4
15,6	18,1	18,1	22,5
6.7~4.4	7.2~4.4	6.7~4.3	6.8~4.2
41.1~50.3	42.5~50.9	42.5~50.9	41.8~51.9
44,4	45,5	45,5	45,8
21.1~30.3	22.5~30.9	22.5~30.9	21.8~31.9
400V 3N~, 50Hz	230V~/1Ph/50Hz	400V 3N~, 50Hz	
0.38~3.37	0.44~4.18	0.46~4.26	0.58~5.76
0.55~4.86	1.91~18.17	0.66~6.15	0.84~8.31
8~10	10~12	10~12	12~18
1146×536×955	1315×536×1060	1315×536×1060	1397×536×1249
119	145	154	186
34/72	14/64	14/64	12/30
1500	2200	2200	3000
0,00003	0,00004	0,00004	0,00006